

Technical datasheet

LINESUR-2258-M-840-1-BL



Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



LED 220-240 V 50-60 Hz
 IP20


CCT 4000 k
CRI 80+

Product technical data

Mains voltage 220 - 240V AC, 50/60Hz
Connection method Plug-in terminal
Dimming type Non-dimmable

IP rating 20
Protection class I
Ambient temperature 0 to +25 °C

Light source LED
Colour temperature 4000k
Color rendering index 80
Rated luminous flux 4,501 lm
Connected load 42.83 W
Luminous efficacy 105.1 lm/W

Ripple 1 %
Inrush current 37 A
Inrush time 188 μs
Optical system Diffuser
Optical part material PMMA
Housing material Aluminium
Surface finish Powder coated

Width 50,00 cm
Height 70,00 cm
Length 2,258.00 cm
Weight 5.50 kg

Service lifetime (L80 B10) 50 000 h
Warranty 5 years

Dimensions



Light distribution

