

Technical datasheet

LINESUR-2820-M-930-1-BL



Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



LED 220-240 V 50-60 Hz IP20  CE CCT 3000 k CRI 90+

Product technical data

Mains voltage 220 - 240V AC, 50/60Hz
 Connection method Plug-in terminal
 Dimming type Non-dimmable

IP rating 20
 Protection class I
 Ambient temperature 0 to +25 °C


Light source LED
 Colour temperature 3000k
 Color rendering index 90
 Rated luminous flux 4,565 lm
 Connected load 56.48 W
 Luminous efficacy 80.8 lm/W

Ripple 2 %
 Inrush current 18 A
 Inrush time 44 μs
 Optical system Diffuser
 Optical part material PMMA
 Housing material Aluminium
 Surface finish Powder coated

Width 50,00 cm
 Height 70,00 cm
 Length 2,820.00 cm
 Weight 6.80 kg

Service lifetime (L80 B10) 50 000 h
 Warranty 5 years

Dimensions



Light distribution

