

Technical datasheet

LINESUR-2258-L-840-1-BL



Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



LED 220-240 V 50-60 Hz IP20   CCT 4000 k CRI 80+

Product technical data

Mains voltage 220 - 240V AC, 50/60Hz
 Connection method Plug-in terminal
 Dimming type Non-dimmable

IP rating 20
 Protection class I
 Ambient temperature 0 to +25 °C


Light source LED
 Colour temperature 4000k
 Color rendering index 80
 Rated luminous flux 5,912 lm
 Connected load 60.01 W
 Luminous efficacy 98.5 lm/W

Ripple 2 %
 Inrush current 18 A
 Inrush time 44 µs
 Optical system Diffuser
 Optical part material PMMA
 Housing material Aluminium
 Surface finish Powder coated

Width 50.00 cm
 Height 70.00 cm
 Length 2,258.00 cm
 Weight 5.50 kg

Service lifetime (L80 B10) 50 000 h
 Warranty 5 years

Dimensions



Light distribution

