

# Technical datasheet

## LINESUR-2820-L-840-1-BL

ARLI

### Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



LED 220-240 V 50-60 Hz IP20   CCT 4000 k CRI 80+

### Product technical data

Mains voltage 220 - 240V AC, 50/60Hz  
 Connection method Plug-in terminal  
 Dimming type Non-dimmable

IP rating 20  
 Protection class I  
 Ambient temperature 0 to +25 °C


Light source LED  
 Colour temperature 4000k  
 Color rendering index 80  
 Rated luminous flux 7,390 lm  
 Connected load 74.87 W  
 Luminous efficacy 98.7 lm/W

Ripple 2 %  
 Inrush current 18 A  
 Inrush time 44 μs  
 Optical system Diffuser  
 Optical part material PMMA  
 Housing material Aluminium  
 Surface finish Powder coated

Width 50,00 cm  
 Height 70,00 cm  
 Length 2,820.00 cm  
 Weight 6.80 kg

Service lifetime (L80 B10) 50 000 h  
 Warranty 5 years

### Dimensions



### Light distribution

