

# Technical datasheet

LINESUS2258-XL-840-1-BL-DI-



## Product description

LINE Suspended is a pendant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. Direct and indirect lighting options with DALI control available. Wide range of cable colors. Ideal for offices and commercial spaces. 5-year warranty.


**LED** 220-240 V 50-60 Hz **IP20** **CCT 4000 k** **CRI 80+**

## Product technical data

Mains voltage	220 - 240V AC, 50/60Hz
Connection method	Plug-in terminal
Dimming type	Non-dimmable
IP rating	20
Protection class	I
Ambient temperature	0 to +25 °C
Light source	LED
Colour temperature	4000k
Color rendering index	80
Rated luminous flux	7,275 lm
Connected load	75.72 W
Luminous efficacy	96.1 lm/W

Ripple	2 %
Inrush current	18 A
Inrush time	44 µs
Optical system	Diffuser
Optical part material	PMMA
Housing material	Aluminium
Surface finish	Powder coated
Width	50.00 cm
Height	70.00 cm
Length	2,258.00 cm
Weight	5.50 kg
Service lifetime (L80 B10)	50 000 h
Warranty	5 years

## Dimensions



## Light distribution



**Available cable colors**

