


Technical datasheet

LINESUS2820-L-840-1-WH-DI-



Product description


LINE Suspended is a pendant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. Direct and indirect lighting options with DALI control available. Wide range of cable colors. Ideal for offices and commercial spaces. 5-year warranty.

LED 220-240 V IP20 CCT 4000 k CRI 80+


Product technical data

Mains voltage	220 - 240V AC, 50/60Hz	Ripple	2 %
Connection method	Plug-in terminal	Inrush current	18 A
Dimming type	Non-dimmable	Inrush time	44 μs
IP rating	20	Optical system	Diffuser
Protection class	I	Optical part material	PMMA
Ambient temperature	0 to +25 °C	Housing material	Aluminium
Light source	LED	Surface finish	Powder coated
Colour temperature	4000k	Width	50.00 cm
Color rendering index	80	Height	70.00 cm
Rated luminous flux	7,390 lm	Length	2,820.00 cm
Connected load	74.87 W	Weight	6.80 kg
Luminous efficacy	98.7 lm/W	Service lifetime (L80 B10)	50 000 h
		Warranty	5 years

Dimensions



Light distribution



Available cable colors

