

# ARLI


LED 220-240 V 50-60 Hz IP20 CE UGR < 19 CCT 3000 K CRI 80+ DIMM Push CLO 

Product technical data			
Mains voltage	220 - 240V AC, 50/60Hz	Ripple	1 %
Connection method	3-phase track adapter	DALI address	1
Dimming type	DALI	Inrush current	6 A
IP rating	20	Inrush time	800 µs
Ambient temperature	0 to +30 °C	Optical system	Lenses
Light source	LED	Optical part material	PMMA
Colour temperature	3000k	Housing material	Aluminium
Color rendering index	80	Surface finish	Powder coated
Rated luminous flux	6 622 lm	Width	62.00 cm
Corrected beam angle	43.5°	Height	57.00 cm
Our track adapter LED luminaire for 3-phase track system with LED source with 60,000 hours lifetime		Length	1,000.00 cm
and high efficiency up to 165 lm/W. Available in 2 lengths and 4 power options, wide range of color		Weight	1.40 kg
temperatures (3000K-6500K) with CRI 80+/90+. Five light distribution types and DALI control option		Service lifetime (L80 B10)	60 000 h
available. Ideal for commercial premises, offices, warehouses and production halls with demanding		Warranty	5 years
visual tasks. 5-year warranty.			

Dimensions




Light distribution



Constant Light Output (CLO)

This system compensates for the depreciation of luminous flux to avoid excess lighting at the beginning of the installation's service life. Luminous depreciation over time must be taken into account to ensure a predefined lighting level during the luminaire's useful life.

Without a CLO feature, this simply means increasing the initial power upon installation in order to make up for luminous depreciation. By precisely controlling the luminous flux, the energy needed to reach the required level can be maintained throughout the luminaire's life.



A. Dimming level  
B. Time  
DALI 2

**DALI** (Digital Addressable Lighting Interface) is an international standard for digital lighting control systems. It enables individual control of each luminaire in the network using digital signals - unlike traditional analog solutions.

**Key DALI2 innovations:**

- Advanced diagnostic capabilities
- Better fault reporting and device status
- Enhanced scene programming options
- Support for RGB/RGBW and tunable white