


# Technical datasheet

## HEXSUR-1200-L-940-1-BL

ARLI

### Product description

The design of the luminaire returns to the power of the basic geometric shapes of the hexagon. By combining several diameters, it is possible to achieve different configurations and lighting scenarios with a great visual impact on the interior.



LED 220-240 V 50-60 Hz IP20   CCT 4000 k CRI 90+

### Product technical data

Mains voltage 220 - 240V AC, 50/60Hz  
 Connection method Plug-in terminal  
 Dimming type Non-dimmable

IP rating 20  
 Protection class I  
 Ambient temperature 0 to +25 °C

Light source LED  
 Colour temperature 4000k  
 Color rendering index 90  
 Rated luminous flux 6,755 lm  
 Connected load 79.25 W  
 Luminous efficacy 85.2 lm/W

Ripple 2 %  
 Inrush current 18 A  
 Inrush time 44 μs  
 Optical system Diffuser  
 Optical part material PMMA  
 Housing material Aluminium  
 Surface finish Powder coated

Width 1,200.00 cm  
 Height 70.00 cm  
 Length 1,200.00 cm  
 Weight 6.40 kg

Service lifetime (L80 B10) 50 000 h  
 Warranty 5 years

### Dimensions

1200



d 1200 mm  
 h 70 mm

### Light distribution

