

# Technical datasheet

## HEXSUR-600-L-930-1-WH




### Product description

The design of the luminaire returns to the power of the basic geometric shapes of the hexagon. By combining several diameters, it is possible to achieve different configurations and lighting scenarios with a great visual impact on the interior.

**LED**    220-240 V    IP20            CCT    CRI  
 50-60 Hz    3000 k    90+

### Product technical data

Mains voltage                    220 - 240V AC, 50/60Hz  
 Connection method            Plug-in terminal  
 Dimming type                    Non-dimmable

IP rating                            20  
 Protection class                I  
 Ambient temperature           0 to +25 °C

Light source                      LED  
 Colour temperature            3000k  
 Color rendering index         90  
 Rated luminous flux            4,396 lm  
 Connected load                 56.90 W  
 Luminous efficacy              77.3 lm/W

Ripple                                1 %  
 Inrush current                    37 A  
 Inrush time                        188 μs  
 Optical system                    Diffuser  
 Optical part material            PMMA  
 Housing material                 Aluminium  
 Surface finish                    Powder coated

Width                                600.00 cm  
 Height                                70.00 cm  
 Length                               600.00 cm  
 Weight                                5.40 kg

Service lifetime (L80 B10)    50 000 h  
 Warranty                            5 years

### Dimensions

**600**



d 600 mm  
h 70 mm

### Light distribution

