

Technical datasheet

WORREC-579-M-940-1-80-WH



Product description

Premium recessed luminaire with precision optics for minimal glare. Ideal for offices, retail spaces and schools where light quality matters. Efficiency up to 141 lm/W, CRI up to 90+, selectable 50° or 80° distribution. Available with DALI control. Lifetime 50,000h, 5-year warranty. Modular sizes 579/859/1139 mm.




LED 220-240 V 50-60Hz IP20  CE  UGR < 19

Product technical data

| | |
|---------------------|------------------------|
| Mains voltage | 220 - 240V AC, 50/60Hz |
| Connection method | Screw terminal |
| Dimming type | Non-dimmable |
| IP rating | 20 |
| Protection class | I |
| Ambient temperature | 0 to +25 °C |
| Light source | LED |
| Rated luminous flux | 2,240 lm |
| Connected load | 20.24 W |
| Luminous efficacy | 110.7 lm/W |

| | |
|----------------------------|---------------|
| Ripple | 3 % |
| Inrush current | 8 A |
| Inrush time | 48 μs |
| Optical system | Lenses |
| Optical part material | PMMA |
| Housing material | Aluminium |
| Surface finish | Powder coated |
| Width | 59.00 cm |
| Height | 53.00 cm |
| Length | 579.00 cm |
| Weight | 1.00 kg |
| Service lifetime (L80 B10) | 50 000 h |
| Warranty | 5 years |

Dimensions



Light distribution

