

Family datasheet

Industry 3 surface




Product description





High-bay led light created with an emphasis on efficiency and easy installation. Suitable for installation in warehouses and production halls.

LED 220-240 V 50-60Hz IP65  


Technical description

Mains voltage	220 - 240V AC, 50/60Hz	Optical system	Lenses
Connection method	Connection cable	Optical part material	PC
IP rating	65	Housing material	Aluminium
Protection class	I	Surface finish	Powder coated
Impact rating	IK 08	Ambient temperature	-25 to 30°C
Light source	LED	Service lifetime (L80 B10)	>100 000h
Switching type	Non-dimmable , DALI	Warranty	7 years
CRI	80		
CCT	4000K, 5000K		
Lumen output	10741-32224 lm		
Efficiency	Up to 164 lm/W		
Power consumption	68-196 W		

Dimensions

S		l 320 mm w 92 mm h 100 mm	L		l 320 mm w 192 mm h 100 mm
M		l 320 mm w 192 mm h 100 mm	XL		l 320 mm w 296 mm h 100 mm

Light distribution curves



Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: **INDSUR3-L-840-1-75**

Attribute	Value	Code
Model	Industry 3 surface	INDSUR3-
Version	S	S
	M	M
	L	L
	XL	XL
CCT	4000k (CRI 80+)	840
	5000k (CRI 80+)	850
Dimming	Non-dimmable	1
	DALI	2
Light distribution	75°	75
	90°	90
	HR	HR
	WHR	WHR