


Family datasheet

Stanley Surface



Product description


Stanley Surface is a large ceiling LED luminaire with high-quality LED source with 50,000 hours lifetime. Available in 5 sizes (500-1200mm), color temperature 4000K with CRI 80+. Surface mounting with DALI control option available. High luminous flux up to 12,169 lm. Ideal for offices and large commercial spaces. 5-year warranty.

LED 220-240 V 50-60 Hz IP20  


Technical description

Mains voltage	220 - 240V AC, 50/60Hz	Optical system	Diffuser
Connection method	Plug-in terminal	Optical part material	PC
IP rating	20	Housing material	Steel
Protection class	I	Surface finish	Powder coated
Light source	LED	Ambient temperature	0 to +25°C
Switching type	Non-dimmable , DALI	Service lifetime (L80 B10)	50 000h
CRI	80	Warranty	5 years
CCT	4000K		
Lumen output	3042-12169 lm		
Efficiency	Up to 76 lm/W		
Power consumption	40-160 W		

Dimensions



Light distribution curves



Default

Available housing colors



RAL 9005 RAL 9003

Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: STYSUS-1000-840-1-BL

Attribute	Value	Code
Model	Stanley Surface	STYSUS-
Size	500	500
	600	600
	800	800
	1000	1000
	1200	1200
CCT	4000k (CRI 80+)	840
Dimming	Non-dimmable	1
	DALI	2
Housing Color	Black	BL
	White	WH