

Technical Data Sheet

Flit Compact S



Product description

The use of state-of-the-art LED technology in conventional office and hall illumination provides a lot of advantages like an optimal light distribution and an increased lifetime all at an affordable price. LED FlatPanels are fully compatible with existing conventional lighting infrastructure, and are the perfect choice for both new and replacement markets.




Technical description

Mains voltage	220 - 240 V AC, 50 - 60Hz
Connection	3-pole
Protection rating	IP 20
Light source	LED
Optical system	Lenses
Wiring	Fix / DALI / Wireless DALI
Diffuser material	Polycarbonate
Housing material	Aluminum
Ambient temperature	-25 °C to +30 °C
Service lifetime (L80, B10)	50 000h
Impact rating	IK 08
Accessories	Track system
Warranty	5 years

Version	CCT	Power consup.	Output	CRI (Ra)	lm / W
S8	3000 k	8 W	1055 lm	80+	132
	4000 k	8 W	1125 lm	80+	140
	5000 k	8 W	1125 lm	80+	140
S13	3000 k	13 W	1795 lm	80+	138
	4000 k	13 W	1910 lm	80+	146
	5000 k	13 W	1910 lm	80+	146
S18	3000 k	18 W	2510 lm	80+	139
	4000 k	18 W	2675 lm	80+	148
	5000 k	18 W	2675 lm	80+	148
S26	3000 k	26 W	3415 lm	80+	131
	4000 k	26 W	3640 lm	80+	140
	5000 k	26 W	3640 lm	80+	140

Dimensions



Optics



■ 0°-180° ■ 90°-270°

110°



■ 0°-180° ■ 90°-270°

60°



■ 0°-180° ■ 90°-270°

30°



■ 0°-180° ■ 90°-270°

SYM



■ 0°-180° ■ 90°-270°

ASYM

Product code

The technical specifications of the luminaire are determined through the combination of 4 categories, which result in a unique product code.

	Value	Code
Model	Flit Compact S	FLIT COM S
Version	S8	8
	S13	13
	S18	18
	S26	26
Color temperature	3000 k	830
	4000 k	840
	5000 k	850
Dimming	Fix	1
	DALI	2
Beam angle	30°	30
	60°	60
	110°	110
	SYM	SYM
	ASYM	ASYM

Configuration example

Track

Luminaire with a power consumption of 8 W that produce a luminous flux of 1125 lm. FIX, 60° optic, color temperature of 4000k

Code: **FLIT COM S 8 840 1 60**