# Technical datasheet

## WOR-S-935-1-SYM-WH



### Product description

Modern recessed lamp with excellent lighting properties. Suitable for lighting offices, corridors and design spaces. The lamp uses the most modern LED technology, which makes the lamp powerful and economical.


LED | 220-240 V 50-60 Hz | IP20 | UGR < 19 | CCT 3500 k | CRI 90+

### Product technical data

| | |
|---|---|
| Mains voltage | 220 - 240V AC, 50/60Hz |
| Connection method | Screw terminal |
| Dimming type | Non-dimmable |
| IP rating | 20 |
| Protection class | II |
| Ambient temperature | 0 to +25 °C |
| Light source | LED |
| Colour temperature | 3500k |
| Color rendering index | 90 |
| Rated luminous flux | 761 lm |
| Connected load | 9.00 W |
| Luminous efficacy | 84.6 lm/W |

| | |
|---|---|
| Ripple | 1 % |
| Inrush current | 10 A |
| Inrush time | 200 µs |
| Optical system | Lenses |
| Optical part material | PMMA |
| Housing material | Steel |
| Surface finish | Powder coated |
| Width | 71.00 cm |
| Height | 41.00 cm |
| Length | 340.00 cm |
| Weight | 0.75 kg |
| Service lifetime (L80 B10) | 50 000 h |
| Warranty | 5 years |

### Dimensions




### Light distribution

