

# Technical datasheet

## WOR-M-927-1-SYM-BL



### Product description

Modern recessed lamp with excellent lighting properties. Suitable for lighting offices, corridors and design spaces. The lamp uses the most modern LED technology, which makes the lamp powerful and economical.



**LED**    220-240 V    IP20                UGR < 19    CCT 2700 k    CRI 90+

### Product technical data

|                       |                        |                            |               |
|-----------------------|------------------------|----------------------------|---------------|
| Mains voltage         | 220 - 240V AC, 50/60Hz | Ripple                     | 1 %           |
| Connection method     | Screw terminal         | Inrush current             | 10 A          |
| Dimming type          | Non-dimmable           | Inrush time                | 200 μs        |
| IP rating             | 20                     | Optical system             | Lenses        |
| Protection class      | II                     | Optical part material      | PMMA          |
| Ambient temperature   | 0 to +25 °C            | Housing material           | Steel         |
| Light source          | LED                    | Surface finish             | Powder coated |
| Colour temperature    | 2700k                  | Width                      | 71.00 cm      |
| Color rendering index | 90                     | Height                     | 41.00 cm      |
| Rated luminous flux   | 823 lm                 | Length                     | 340.00 cm     |
| Connected load        | 10.99 W                | Weight                     | 0.75 kg       |
| Luminous efficacy     | 74.9 lm/W              | Service lifetime (L80 B10) | 50 000 h      |
|                       |                        | Warranty                   | 5 years       |

### Dimensions



### Light distribution

