

# Technical datasheet

## LINESUR-572-S-830-1-BL



### Product description

LINE Surface is an elegant linear LED luminaire with high-quality LED source with 50,000 hours lifetime and PMMA diffuser for uniform light. Available in 5 sizes (572-2820mm), color temperatures 3000K/4000K with CRI 80+/90+. DALI control option available. Ideal for offices and commercial spaces. 5-year warranty.



**LED** 220-240 V 50-60 Hz **IP20**   **CCT 3000 k** **CRI 80+**

### Product technical data

**Mains voltage** 220 - 240V AC, 50/60Hz  
**Connection method** Plug-in terminal  
**Dimming type** Non-dimmable

**IP rating** 20  
**Protection class** I  
**Ambient temperature** 0 to +25 °C


**Light source** LED  
**Colour temperature** 3000k  
**Color rendering index** 80  
**Rated luminous flux** 718 lm  
**Connected load** 8.07 W  
**Luminous efficacy** 89.0 lm/W

**Ripple** 3 %  
**Inrush current** 17 A  
**Inrush time** 118 μs  
**Optical system** Diffuser  
**Optical part material** PMMA  
**Housing material** Aluminium  
**Surface finish** Powder coated

**Width** 50.00 cm  
**Height** 70.00 cm  
**Length** 572.00 cm  
**Weight** 1.23 kg

**Service lifetime (L80 B10)** 50 000 h  
**Warranty** 5 years

### Dimensions



### Light distribution

