

# Technical datasheet

## GEMINYM-840-1-WH-




### Product description

Geminy linear lamp is designed to create smaller atmospheres within larger spaces. The design features elegant lines and subtle details, along with copper details that complement the structure of the lamp and provide a rich material contrast to powder-coated parts, creating a modern and functional light for any space.


**LED** 220-240 V 50-60 Hz **IP20**  **CE** **CCT 4000 k** **CRI 80+**

### Product technical data


Mains voltage	220 - 240V AC, 50/60Hz
Connection method	Plug-in terminal
Dimming type	Non-dimmable
IP rating	20
Protection class	I
Ambient temperature	0 to +25 °C
Light source	LED
Colour temperature	4000k
Color rendering index	80
Rated luminous flux	3,260 lm
Connected load	23.48 W
Luminous efficacy	138.9 lm/W

Ripple	1 %
Inrush current	18 A
Inrush time	154 μs
Optical system	Diffuser
Optical part material	PMMA
Housing material	Steel
Surface finish	Powder coated
Width	40.00 cm
Height	40.00 cm
Length	1,200.00 cm
Weight	4.00 kg
Service lifetime (L80 B10)	50 000 h
Warranty	5 years

### Dimensions



### Light distribution



**Available cable colors**

