Family datasheet

Trium



Product description

Linear LED luminaire rated IP69K. Built for food processing and industrial facilities that clean with pressure and steam. 5-year warranty.

LED 220-240V 50-60Hz IP69k

Technical description

Mains voltage	220 - 240V AC, 50/60Hz
Connection method	Connection cable
IP rating	69k
Protection class	I
Impact rating	IK 10
Light source	LED
Switching type	Non-dimmable
CRI	80
CCT	4000K
Lumen output	5600-8000 lm
Efficiency	Up to 144 lm/W
Power consumption	38-55 W

Optical system	Diffuser
Optical part material	PMMA
Housing material	Plastic
Ambient temperature	-20 to +45°C
Service lifetime (L70 B10)	102 000h
Warranty	5 years

Dimensions




S

L	1200 mm
W	81 mm
H	81 mm
NW	1.9 kg

M

L	1500 mm
W	81 mm
H	81 mm
NW	2.3 kg

Light distribution curves



Default

Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: **TRIUM-M-840-1**

Attribute	Value	Code
Model	Trium	TRIUM-
Version	S	S
	M	M
CCT	4000k (CRI 80+)	840
Dimming	Non-dimmable	1