Family datasheet

Base Linear 65



Product description

A linear luminaire for demanding environments. IP65 and IK08 ratings make it suitable for dusty, damp and cold conditions. A reliable choice for warehouses, workshops, garages and production halls. Part of the Base range. Standard version without configuration, at a price that holds up in budget-driven projects.


LED 220-240V 50-60Hz IP65

Technical description

Mains voltage	220 - 240V AC, 50/60Hz
Connection method	Plug-in terminal
IP rating	65
Protection class	II
Impact rating	IK 08
Light source	LED
Switching type	Non-dimmable
CRI	80
CCT	4000K
Lumen output	5040-9800 lm
Efficiency	Up to 140 lm/W
Power consumption	36-70 W

Optical system	Diffuser
Optical part material	PC
Housing material	Plastic
Ambient temperature	0 to +30°C
Service lifetime (L80 B30)	80000h
Warranty	5 years


Dimensions



S
L 1200 mm
W 70 mm
H 50 mm

M/L
L 1500 mm
W 70 mm
H 50 mm

Light distribution curves



Default

Product codes

The technical specifications of the luminaire are determined through the combination of these attributes, which result in a unique product code.

Order code example: **BASELIN-L-840-1**

Attribute	Value	Code
Model	Base Linear 65	BASELIN-
Version	S	S
	M	M
	L	L
CCT	4000k (CRI 80+)	840
Dimming	Non-dimmable	1